


Rundzylinder

nach ISO 6432, Ø 8 - 25

PLUS



1.DMD.25050

Rundzylinder, doppeltwirkend, mit Magnet, mit einstellbarer Dämpfung

Artikel Nr.	Typen Nr.	Kolben-Ø mm	Hub mm	Anschluss	Kolbenstangengewinde
105796	1.DMD.16010	16	10	M5	M6
105797	1.DMD.16025	16	25	M5	M6
105798	1.DMD.16050	16	50	M5	M6
105799	1.DMD.16080	16	80	M5	M6
105800	1.DMD.16100	16	100	M5	M6
105801	1.DMD.16125	16	125	M5	M6
105802	1.DMD.16160	16	160	M5	M6
105803	1.DMD.16200	16	200	M5	M6
105804	1.DMD.20010	20	10	G 1/8	M8
105805	1.DMD.20025	20	25	G 1/8	M8
105806	1.DMD.20050	20	50	G 1/8	M8
105807	1.DMD.20080	20	80	G 1/8	M8
105808	1.DMD.20100	20	100	G 1/8	M8
105809	1.DMD.20125	20	125	G 1/8	M8
105810	1.DMD.20160	20	160	G 1/8	M8
105811	1.DMD.20200	20	200	G 1/8	M8
105812	1.DMD.20250	20	250	G 1/8	M8
105813	1.DMD.25010	25	10	G 1/8	M10x1,25
105814	1.DMD.25025	25	25	G 1/8	M10x1,25
105815	1.DMD.25050	25	50	G 1/8	M10x1,25
105816	1.DMD.25080	25	80	G 1/8	M10x1,25
105817	1.DMD.25100	25	100	G 1/8	M10x1,25
105818	1.DMD.25125	25	125	G 1/8	M10x1,25
105819	1.DMD.25160	25	160	G 1/8	M10x1,25
105820	1.DMD.25200	25	200	G 1/8	M10x1,25
105821	1.DMD.25250	25	250	G 1/8	M10x1,25



1.EM.20050

Rundzylinder, einfachwirkend (drucklos eingefahren), mit Magnet, ohne einstellbare Dämpfung

Artikel Nr.	Typen Nr.	Kolben-Ø mm	Hub mm	Anschluss	Kolbenstangengewinde
105822	1.EM.08010	8	10	M5	M4
105823	1.EM.08025	8	25	M5	M4
105824	1.EM.08050	8	50	M5	M4
105825	1.EM.10010	10	10	M5	M4
105826	1.EM.10025	10	25	M5	M4
105827	1.EM.10050	10	50	M5	M4
105828	1.EM.12010	12	10	M5	M6
105829	1.EM.12025	12	25	M5	M6
105830	1.EM.12050	12	50	M5	M6
105831	1.EM.16010	16	10	M5	M6
105832	1.EM.16025	16	25	M5	M6
105833	1.EM.16050	16	50	M5	M6



**NICHT DAS PASSENDE
GEFUNDEN?**

Alle Produktvarianten, Dokumentation und weitere Informationen erhalten Sie auf Anfrage.