

Reduzierstücke

Serie »speedfit«


PLUS



77.1210

Reduzierstück

Artikel Nr.	Typen Nr.	Stutzen mm	für Schlauch- Außen-Ø mm	Arbeitsdruck bar	L1 mm
136485	77.0806	8	6	-0,95 - 16	37,4
136486	77.1006	10	6	-0,95 - 16	40,5
136487	77.1008	10	8	-0,95 - 16	40,4
110328	77.1208	12	8	-0,95 - 16	40,5
110329	77.1210	12	10	-0,95 - 10	50,0
110330	77.1510	15	10	-0,95 - 10	55,3
110331	77.1512	15	12	-0,95 - 10	60,2
110332	77.1815	18	15	-0,95 - 10	70,5
110333	77.2215	22	15	-0,95 - 10	69,6
110334	77.2218	22	18	-0,95 - 10	71,6
110335	77.2815	28	15	-0,95 - 10	80,2
110336	77.2822	28	22	-0,95 - 10	81,8



Einsteck-Winkelverbinder

Serie »speedfit«


PLUS



78.0606

Einsteck-Winkelverbinder

Artikel Nr.	Typen Nr.	Stutzen mm	für Schlauch- Außen-Ø mm	Arbeitsdruck bar	L1 mm	L2 mm
110339	78.0404	4	4	-0,95 - 16	26,0	22,0
110340	78.0505	5	5	-0,95 - 16	26,0	22,0
110341	78.0606	6	6	-0,95 - 16	29,0	25,0
110342	78.0808	8	8	-0,95 - 16	32,0	27,0
110343	78.1010	10	10	-0,95 - 10	35,5	32,0
110344	78.1212	12	12	-0,95 - 10	46,0	39,0
110345	78.1515	15	15	-0,95 - 10	52,1	42,2
110346	78.1818	18	18	-0,95 - 10	56,5	41,0
136479	78.2222	22	22	-0,95 - 10	58,7	67,0



Einschraubstutzen

Serie »speedfit«

PLUS



75.012-10

Einschraub-Stutzen (Parallelgewinde)

Artikel Nr.	Typen Nr.	Gewinde	für Schlauch- Außen-Ø mm	Arbeitsdruck bar	L1 mm	SW mm
136494	75.018-4	G 1/8	4	-0,95 - 16	25,5	14
136495	75.018-5	G 1/8	5	-0,95 - 16	25,5	14
136496	75.018-6	G 1/8	6	-0,95 - 16	27,5	15
136497	75.018-8	G 1/8	8	-0,95 - 16	28,5	17
136498	75.014-4	G 1/4	4	-0,95 - 16	29,0	17
136499	75.014-5	G 1/4	5	-0,95 - 16	29,0	17
136500	75.014-6	G 1/4	6	-0,95 - 16	30,0	17
136501	75.014-8	G 1/4	8	-0,95 - 16	31,0	17
136502	75.014-10	G 1/4	10	-0,95 - 10	34,0	20
136503	75.038-8	G 3/8	8	-0,95 - 16	32,5	22



**NICHT DAS PASSENDE
GEFUNDEN?**

Alle Produktvarianten, Dokumenta-
tion und weitere Informationen
erhalten Sie auf Anfrage.