





KAMLOK-Schlauchkupplungen


Aluminium, gemäß Norm A-A 59326 25.09.98 (früher MIL - C 27487)




1116.10



1117.112



1118.112



1119.20

Kamlok-Verschlusskappe für Schnellkupplungsstecker, Typ DC

Artikel Nr.	Typen Nr.	BG	für Stecker-Ø mm	A mm	C mm
108055	1115.212	2 1/2	76	109,5	77,5
108056	1115.30	3	92	131,8	76,5
108057	1115.40	4	120	159,9	78,0

Kamlok-Schnellkupplungsstecker mit Außengewinde, Typ F

Artikel Nr.	Typen Nr.	Gewinde	Stecker-Ø mm	L mm
108058	1116.34	R 3/4	32	55,0
108059	1116.10	R 1	37	67,8
108060	1116.114	R 1 1/4	45	78,0
108061	1116.112	R 1 1/2	53	76,0
108062	1116.20	R 2	63	83,5
108063	1116.212	R 2 1/2	76	97,0
108064	1116.30	R 3	92	99,5
108065	1116.40	R 4	120	104,5

Kamlok-Schnellkupplungsstecker mit Innengewinde, Typ A

Artikel Nr.	Typen Nr.	Gewinde	Stecker-Ø mm	L mm
108066	1117.34	G 3/4	32	41,0
108067	1117.10	G 1	37	50,8
108068	1117.114	G 1 1/4	45	55,0
108069	1117.112	G 1 1/2	53	56,0
108070	1117.20	G 2	63	59,0
108071	1117.212	G 2 1/2	76	79,2
108072	1117.30	G 3	92	71,7
108073	1117.40	G 4	120	71,2

Kamlok-Schnellkupplungsstecker mit Schlauchtülle, Typ E

Artikel Nr.	Typen Nr.	für Schlauch-Innen-Ø	Stecker-Ø mm	L mm
108074	1118.34	19	32	85,3
108075	1118.10	25	37	100,8
108076	1118.114	32	45	109,0
108077	1118.112	38	53	123,5
108078	1118.20	50	63	142,0
108079	1118.212	63	76	150,5
108080	1118.30	75	92	157,0
108081	1118.40	100	120	166,0

Kamlok-Verschlussstecker, Typ DP

Artikel Nr.	Typen Nr.	BG	Stecker-Ø mm	A mm	C mm
108082	1119.34	3/4	32	32,1	38,0
108083	1119.10	1	37	36,6	52,3
108084	1119.114	1 1/4	45	45,4	57,5
108085	1119.112	1 1/2	53	53,4	57,0
108086	1119.20	2	63	63,0	63,5
108087	1119.212	2 1/2	76	57,7	67,5
108088	1119.30	3	92	91,4	67,5
108089	1119.40	4	120	119,5	69,8

NICHT DAS PASSENDE GEFUNDEN?

Alle Produktvarianten, Dokumentation und weitere Informationen erhalten Sie auf Anfrage.