



Dichtringe

aus Vulkanfiber, Polyamid, Aluminium, Kupfer, PTFE, PVC oder PA6



258.04/1

Dichtring aus Vulkanfiber, Temperatur bis max. 75 °C

Artikel Nr.	Typen Nr.	für Gewinde	Material	D mm	D1 mm	H mm
114081	258.00	M5	Vulkanfiber	5,1	8,0	1,0
114082	258.01	G 1/8	Vulkanfiber	10,0	13,0	1,5
114083	258.02	G 1/4	Vulkanfiber	13,2	18,0	1,5
114084	258.03	G 3/8	Vulkanfiber	16,8	22,0	1,5
114085	258.04	G 1/2	Vulkanfiber	21,0	28,0	2,0
114086	258.04/1	G 3/4	Vulkanfiber	26,5	33,0	2,0
114087	258.04/2	G 1	Vulkanfiber	33,3	38,9	2,0



258.10

Dichtring aus Polyamid, Temperatur bis max. 80 °C

Artikel Nr.	Typen Nr.	für Gewinde	Material	D mm	D1 mm	H mm
114088	258.05	M5	Polyamid	5,1	8,0	1,0
114089	258.06	G 1/8	Polyamid	10,0	13,0	1,5
114090	258.07	G 1/4	Polyamid	13,2	18,0	1,5
114091	258.08	G 3/8	Polyamid	16,8	22,0	1,5
114092	258.09	G 1/2	Polyamid	21,0	28,0	1,5
114093	258.10	G 3/4	Polyamid	26,8	33,0	2,0
114094	258.10/1	G 1	Polyamid	33,3	38,9	2,0



258.16

Dichtring aus Aluminium, Temperatur bis max. 250 °C

Artikel Nr.	Typen Nr.	für Gewinde	Material	D mm	D1 mm	H mm
114095	258.11	M5	Aluminium	5,1	8,0	1,0
114096	258.12	G 1/8	Aluminium	10,0	13,8	1,5
114097	258.13	G 1/4	Aluminium	13,3	18,0	1,5
114098	258.14	G 3/8	Aluminium	17,0	21,8	1,5
114099	258.15	G 1/2	Aluminium	21,0	28,0	1,5
114100	258.16	G 3/4	Aluminium	26,5	33,0	2,0
114101	258.17	G 1	Aluminium	33,3	38,9	2,0



258.33

Dichtring aus Kupfer, Temperatur bis max. 250 °C

Artikel Nr.	Typen Nr.	für Gewinde	Material	D mm	D1 mm	H mm
114102	258.30	M5	Kupfer	5,2	8,0	1,0
114103	258.31	G 1/8	Kupfer	10,2	13,4	1,5
114104	258.32	G 1/4	Kupfer	13,2	17,9	1,5
114105	258.33	G 3/8	Kupfer	16,8	22,0	1,5
114106	258.34	G 1/2	Kupfer	21,2	27,9	1,5
114107	258.35	G 3/4	Kupfer	26,5	33,0	2,0
114108	258.36	G 1	Kupfer	33,3	38,9	2,0



258.45

Dichtring aus PTFE, Temperatur bis max. 260 °C

Artikel Nr.	Typen Nr.	für Gewinde	Material	D mm	D1 mm	H mm
114109	258.40	M5	PTFE	5,1	8,0	1,0
114110	258.41	G 1/8	PTFE	10,0	13,0	1,5
114111	258.42	G 1/4	PTFE	13,2	18,0	1,5
114112	258.43	G 3/8	PTFE	16,8	22,0	1,5
114113	258.44	G 1/2	PTFE	21,0	28,0	1,5
114114	258.45	G 3/4	PTFE	26,5	33,0	2,0
114115	258.46	G 1	PTFE	33,3	38,9	2,0



**NICHT DAS PASSENDE
GEFUNDEN?**

Alle Produktvarianten, Dokumentation und weitere Informationen erhalten Sie auf Anfrage.