

Gerade Einschraubverschraubungen

Stahl verzinkt nach DIN 2353



Gerade Einschraubverschraubung, Außengewinde zylindrisch, leichte Ausführung


Artikel Nr.	Typen Nr.	Gewinde	Rohr-Außen-Ø mm	PN bar	L1 mm	L2 mm	SW 1 mm	SW 2 mm
159566	GE148LST	G 1/4	8	315	37,0	12,0	17	19
159567	GE388LST	G 3/8	8	315	38,0	12,0	17	22
159568	GE128LST	G 1/2	8	315	41,0	14,0	17	27
159569	GE1810LST	G 1/8	10	315	34,0	8,0	19	17
159570	GE1410LST	G 1/4	10	315	38,0	12,0	19	19
159571	GE3810LST	G 3/8	10	315	39,0	12,0	19	22
159572	GE1210LST	G 1/2	10	315	42,0	14,0	19	27
159573	GE1412LST	G 1/4	12	315	39,0	12,0	22	19
159574	GE3812LST	G 3/8	12	315	39,0	12,0	22	22
159575	GE1212LST	G 1/2	12	315	42,0	14,0	22	27
159576	GE3412LST	G 3/4	12	315	45,0	16,0	22	32
159577	GE3815LST	G 3/8	15	315	41,0	12,0	27	24
159578	GE1215LST	G 1/2	15	315	43,0	14,0	27	27
159579	GE3415LST	G 3/4	15	315	46,0	16,0	27	32
159580	GE3818LST	G 3/8	18	315	41,0	12,0	32	27
159581	GE1218LST	G 1/2	18	315	45,0	14,0	32	27
159582	GE3418LST	G 3/4	18	315	46,0	16,0	32	32
159583	GE1222LST	G 1/2	22	160	47,0	14,0	36	32
159584	GE3422LST	G 3/4	22	160	49,0	16,0	36	32
159585	GE122LST	G 1	22	160	52,0	18,0	36	41



GE146SST

Gerade Einschraubverschraubung, Außengewinde zylindrisch, schwere Ausführung

Artikel Nr.	Typen Nr.	Gewinde	Rohr-Außen-Ø mm	PN bar	L1 mm	L2 mm	SW 1 mm	SW 2 mm
159586	GE146SST	G 1/4	6	630	40,0	12,0	17	19
159587	GE126SST	G 1/2	6	630	47,0	14,0	17	27
159588	GE148SST	G 1/4	8	630	42,0	12,0	19	19
159589	GE388SST	G 3/8	8	630	42,0	12,0	19	22
159590	GE1410SST	G 1/4	10	630	43,0	12,0	22	19
159591	GE3810SST	G 3/8	10	630	43,0	12,0	22	22
159592	GE1210SST	G 1/2	10	630	48,0	14,0	22	27
159593	GE1412SST	G 1/4	12	630	45,0	12,0	24	22
159594	GE3812SST	G 3/8	12	630	45,0	12,0	24	22
159595	GE1212SST	G 1/2	12	630	48,0	14,0	24	27
159596	GE3814SST	G 3/8	14	630	48,0	12,0	27	24
159597	GE1214SST	G 1/2	14	630	51,0	14,0	27	27
159598	GE3816SST	G 3/8	16	400	48,0	12,0	30	27
159599	GE1216SST	G 1/2	16	400	51,0	14,0	30	27
159600	GE3416SST	G 3/4	16	400	55,0	16,0	30	32
159601	GE1220SST	G 1/2	20	400	56,0	14,0	36	32
159602	GE3420SST	G 3/4	20	400	58,0	16,0	36	32
159603	GE3425SST	G 3/4	25	400	63,0	16,0	46	41
159604	GE125SST	G 1	25	400	65,0	18,0	46	41



V 28-ZW

Gerade Einschraubverschraubung, Außengewinde zylindrisch, weichdichtend, leichte Ausführung

Artikel Nr.	Typen Nr.	Gewinde	Rohr-Außen-Ø mm	PN bar	L1 mm	L2 mm	SW 1 mm	SW 2 mm
112249	V 25-ZW	G 1/8	6	315	31,0	8,0	14	14
112251	V 28-ZW	G 1/4	6	315	37,0	12,0	14	19
112255	V 33-ZW	G 3/8	6	315	38,0	12,0	14	22
112250	V 26-ZW	G 1/8	8	315	32,0	8,0	17	14
112252	V 29-ZW	G 1/4	8	315	37,0	12,0	17	19
112256	V 34-ZW	G 3/8	8	315	38,0	12,0	17	22
112260	V 38-ZW	G 1/2	8	315	41,0	14,0	17	27
159605	GE1810LSTNBR	G 1/8	10	315	34,0	8,0	19	17



**NICHT DAS PASSENDE
GEFUNDEN?**

Alle Produktvarianten, Dokumen-
tation und weitere Informationen
erhalten Sie auf Anfrage.