


# T-Stücke

Messing vernickelt

**PLUS** ||



## T-Stück, innen/innen/innen, zylindrisch nach DIN EN ISO 228-1

Artikel Nr.	Typen Nr.	Gewinde	L1 mm	L2 mm	SW mm
112765	N 254.32	M5	22,0	11,0	9
112766	N 254.33	G 1/8	42,0	21,0	10
112767	N 254.34	G 1/4	51,0	25,5	13
112768	N 254.35	G 3/8	56,0	28,0	17
112769	N 254.39	G 1/2	67,0	33,5	21
112770	N 254.48	G 3/4	73,0	36,5	25
112771	N 254.49	G 1	90,0	45,0	30



N 254.34

## T-Stück, innen/außen/innen, AG: konisch DIN 2999, IG: zyl. nach DIN EN ISO 228-1

Artikel Nr.	Typen Nr.	Gewinde	L1 mm	L2 mm	SW mm
112772	N 254.40	M5	22,0	11,5	9
112773	N 254.41	G/R 1/8	42,0	18,5	10
112774	N 254.42	G/R 1/4	51,0	23,5	13
112775	N 254.43	G/R 3/8	56,0	26,0	17
112776	N 254.44	G/R 1/2	67,0	31,0	21
112777	N 254.45	G/R 3/4	73,0	33,0	25
112778	N 254.46	G/R 1	90,0	39,0	30



N 254.42

## T-Stück, innen/innen/außen, AG: konisch DIN 2999, IG: zyl. nach DIN EN ISO 228-1

Artikel Nr.	Typen Nr.	Gewinde	L1 mm	L2 mm	SW mm
112779	N 254.70	M5	22,5	11,0	9
112780	N 254.71	G/R 1/8	39,5	21,0	10
112781	N 254.72	G/R 1/4	49,0	23,5	13
112782	N 254.73	G/R 3/8	54,0	28,0	17
112783	N 254.74	G/R 1/2	64,5	33,5	21
112784	N 254.75	G/R 3/4	69,5	36,5	25
112785	N 254.76	G/R 1	84,0	45,0	30



N 254.72

## T-Stück, außen/innen/außen, AG: konisch DIN 2999, IG: zyl. nach DIN EN ISO 228-1

Artikel Nr.	Typen Nr.	Gewinde	L1 mm	L2 mm	SW mm
112786	N 254.81	G/R 1/8	37,0	21,0	10
112787	N 254.82	G/R 1/4	47,0	25,5	13
112788	N 254.83	G/R 3/8	52,0	28,0	17
112789	N 254.84	G/R 1/2	62,0	33,5	21
112790	N 254.85	G/R 3/4	66,5	36,5	25
112791	N 254.86	G/R 1	78,0	45,0	30



N 254.82

## T-Stück, außen/außen/innen, AG: konisch DIN 2999, IG: zyl. nach DIN EN ISO 228-1

Artikel Nr.	Typen Nr.	Gewinde	L1 mm	L2 mm	SW mm
112792	N 254.91	G/R 1/8	39,5	18,5	10
112793	N 254.92	G/R 1/4	49,0	23,5	13
112794	N 254.93	G/R 3/8	54,0	26,0	17
112795	N 254.94	G/R 1/2	64,5	31,0	21
112796	N 254.95	G/R 3/4	69,5	33,0	25
112797	N 254.96	G/R 1	84,0	39,0	30



N 254.92



**NICHT DAS PASSENDE  
GEFUNDEN?**

Alle Produktvarianten, Dokumentation und weitere Informationen erhalten Sie auf Anfrage.