

Rohrdoppelnippel

EASY

Material	Messing blank
Arbeitsdruck max.	10 bar
Mediumtemperatur max.	90 °C
Umgebungstemperatur max.	90 °C

Rohrdoppelnippel, Messing

Artikel Nr.	Typen Nr.	Gewinde	Länge mm
111056	LN 1230	G 1/2	30,0
111057	LN 1240	G 1/2	40,0
111058	LN 1250	G 1/2	50,0
111059	LN 1260	G 1/2	60,0
111060	LN 1280	G 1/2	80,0
111061	LN 12100	G 1/2	100,0
111062	LN 12120	G 1/2	120,0
111063	LN 12150	G 1/2	150,0
111064	LN 12180	G 1/2	180,0
111065	LN 12200	G 1/2	200,0
111066	LN 3440	G 3/4	40,0
111067	LN 3460	G 3/4	60,0
111068	LN 3480	G 3/4	80,0
111069	LN 34100	G 3/4	100,0
111070	LN 34120	G 3/4	120,0
111071	LN 34150	G 3/4	150,0
111072	LN 34180	G 3/4	180,0
111073	LN 34200	G 3/4	200,0
111074	LN 10040	G 1	40,0
111075	LN 10060	G 1	60,0
111076	LN 10080	G 1	80,0
111077	LN 100100	G 1	100,0
111078	LN 100120	G 1	120,0
111079	LN 100150	G 1	150,0
111080	LN 100180	G 1	180,0
111081	LN 100200	G 1	200,0
111082	LN 11460	G 1 1/4	60,0
111083	LN 11480	G 1 1/4	80,0
111084	LN 114100	G 1 1/4	100,0
111085	LN 114120	G 1 1/4	120,0
111086	LN 114150	G 1 1/4	150,0
111087	LN 114180	G 1 1/4	180,0
111088	LN 114200	G 1 1/4	200,0
111089	LN 11260	G 1 1/2	60,0
111090	LN 11280	G 1 1/2	80,0
111091	LN 112100	G 1 1/2	100,0
111092	LN 112120	G 1 1/2	120,0
111093	LN 112150	G 1 1/2	150,0
111094	LN 112200	G 1 1/2	200,0
111095	LN 20060	G 2	60,0
111096	LN 20080	G 2	80,0
111097	LN 200100	G 2	100,0
111098	LN 200120	G 2	120,0
111099	LN 200150	G 2	150,0
111100	LN 200200	G 2	200,0



LN 1280



 **NICHT DAS PASSENDE
GEFUNDEN?**

Alle Produktvarianten, Dokumenta-
tion und weitere Informationen
erhalten Sie auf Anfrage.