

Kreuzstücke

Messing vernickelt

PLUS



N 255.02



N 255.12

Kreuzstück, 4 x innen, zylindrisch nach DIN EN ISO 228-1

Artikel Nr.	Typen Nr.	Gewinde	L1 mm	L2 mm	SW mm
112798	N 255.01	G 1/8	21,0	42,0	10
112799	N 255.02	G 1/4	25,5	51,0	13
112800	N 255.03	G 3/8	28,0	56,0	17
112801	N 255.04	G 1/2	33,5	67,0	21


Kreuzstück, 3 x innen, 1 x außen, AG: kon. DIN 2999, IG: zyl. DIN EN ISO 228-1

Artikel Nr.	Typen Nr.	Gewinde	L1 mm	L2 mm	SW mm
112802	N 255.11	G/R 1/8	18,5	42,0	10
112803	N 255.12	G/R 1/4	23,5	51,0	13
112804	N 255.13	G/R 3/8	26,0	56,0	17
112805	N 255.14	G/R 1/2	31,0	67,0	21

Anschlussstücke

Messing blank

Betriebsdruck max.	60 bar
Betriebstemperatur max.	150 °C



Winkelstücke

Messing blank

PLUS



253.01



253.12

Winkelstück, außen/außen, konisch nach DIN 2999

Artikel Nr.	Typen Nr.	Gewinde	L1 mm	L2 mm	SW mm
112696	253.00	R 1/8	18,5	18,5	10
112697	253.01	R 1/4	23,5	23,5	13
112698	253.02	R 3/8	26,0	26,0	17
112699	253.03	R 1/2	31,0	31,0	21
112700	253.04	R 3/4	33,0	33,0	25
112701	253.05	R 1	39,0	39,0	30

Winkelstück, innen/innen, zylindrisch nach DIN EN ISO 228-1

Artikel Nr.	Typen Nr.	Gewinde	L1 mm	L2 mm	SW mm
112702	253.11	G 1/8	21,0	21,0	10
112703	253.12	G 1/4	25,5	25,5	13
112704	253.13	G 3/8	28,0	28,0	17
112705	253.14	G 1/2	33,5	33,5	21
112706	253.32	G 3/4	36,5	36,5	25
112707	253.33	G 1	45,0	45,0	30



**NICHT DAS PASSENDE
GEFUNDEN?**

Alle Produktvarianten, Dokumentation und weitere Informationen erhalten Sie auf Anfrage.