

TVR148SST


T-Einschraubverschraubungen

Stahl verzinkt nach DIN 2353



T-Einschraubverschraubung, Außengewinde konisch nach ISO 7-1, schwere Ausführung

Artikel Nr.	Typen Nr.	Gewinde	Rohr-Außen-Ø mm	PN bar	L1 mm	L2 mm	SW 1 mm	SW 2 mm
112187	V 116	R 1/4	6	630	31,0	26,0	17	12
159206	TVR148SST	R 1/4	8	630	32,0	27,0	19	14
159207	TVR3810SST	R 3/8	10	630	34,0	28,0	22	17
159208	TVR3812SST	R 3/8	12	630	38,0	31,0	24	17
159209	TVR1214SST	R 1/2	14	630	40,0	32,0	27	19
159210	TVR1216SST	R 1/2	16	400	43,0	32,0	30	24
159211	TVR3420SST	R 3/4	20	400	48,0	42,0	36	27
159212	TVR125SST	R 1	25	400	54,0	48,0	46	36



TV10SLST

T-Verschraubungen

Stahl verzinkt nach DIN 2353



T-Verschraubung, sehr leichte Ausführung

Artikel Nr.	Typen Nr.	Rohr-Außen-Ø mm	PN bar	L1 mm	SW 1 mm	SW 2 mm
112194	V 130	4	100	21,0	10	9
112195	V 131	5	100	21,0	12	9
112196	V 132	6	100	21,0	12	9
112197	V 133	8	100	23,0	14	12
159213	TV10SLST	10	100	27,0	17	14
159214	TV12SLST	12	100	25,0	19	17



V 136

T-Verschraubung, leichte Ausführung

Artikel Nr.	Typen Nr.	Rohr-Außen-Ø mm	PN bar	L1 mm	SW 1 mm	SW 2 mm
112198	V 135	6	315	27,0	14	12
112199	V 136	8	315	29,0	17	12
112200	V 137	10	315	30,0	19	14
112201	V 138	12	315	32,0	22	17
112202	V 139	15	315	36,0	27	19
112203	V 140	18	315	40,0	32	24
112204	V 141	22	160	44,0	36	27
159215	TV28LST	28	160	47,0	41	36



TV6SST

T-Verschraubung, schwere Ausführung

Artikel Nr.	Typen Nr.	Rohr-Außen-Ø mm	PN bar	L1 mm	SW 1 mm	SW 2 mm
159216	TV6SST	6	630	31,0	17	12
159217	TV8SST	8	630	32,0	19	14
159218	TV10SST	10	630	34,0	22	17
159219	TV12SST	12	630	38,0	24	17
159220	TV14SST	14	630	40,0	27	19
159221	TV16SST	16	400	43,0	30	24
159222	TV20SST	20	400	48,0	36	27
159223	TV25SST	25	400	54,0	46	36



**NICHT DAS PASSENDE
GEFUNDEN?**

Alle Produktvarianten, Dokumen-
tation und weitere Informationen
erhalten Sie auf Anfrage.