


Winkelstücke

Messing blank

PLUS

Winkelstück, innen/außen, AG: kon. nach DIN 2999, IG: zyl. nach DIN EN ISO 228-1

Artikel Nr.	Typen Nr.	Gewinde	L1 mm	L2 mm	SW mm
112708	253.15	G/R 1/8	18,5	21,0	10
112709	253.16	G/R 1/4	23,5	25,5	13
112710	253.17	G/R 3/8	26,0	28,0	17
112711	253.18	G/R 1/2	31,0	33,5	21
112712	253.19	G/R 3/4	33,0	36,5	25
112713	253.20	G/R 1	39,0	45,0	30



253.17


T-Stücke

Messing blank

PLUS

T-Stück, außen/außen/außen, konisch nach DIN 2999

Artikel Nr.	Typen Nr.	Gewinde	L1 mm	L2 mm	SW mm
112714	254.02	R 1/8	37,0	18,5	10
112715	254.03	R 1/4	47,0	23,5	13
112716	254.04	R 3/8	52,0	26,0	17
112717	254.05	R 1/2	62,0	31,0	21
112718	254.06	R 3/4	66,4	33,0	25
112719	254.07	R 1	78,0	39,0	30



254.03

T-Stück, innen/innen/innen, zylindrisch nach DIN EN ISO 228-1

Artikel Nr.	Typen Nr.	Gewinde	L1 mm	L2 mm	SW mm
112720	254.33	G 1/8	42,0	21,0	10
112721	254.34	G 1/4	51,0	25,5	13
112722	254.35	G 3/8	56,0	28,0	17
112723	254.39	G 1/2	67,0	33,5	21
112724	254.48	G 3/4	73,0	36,5	25
112725	254.49	G 1	90,0	45,0	30



254.34

T-Stück, innen/außen/innen, AG: konisch DIN 2999, IG: zyl. nach DIN EN ISO 228-1

Artikel Nr.	Typen Nr.	Gewinde	L1 mm	L2 mm	SW mm
112726	254.41	G/R 1/8	42,0	18,5	10
112727	254.42	G/R 1/4	51,0	23,5	13
112728	254.43	G/R 3/8	56,0	26,0	17
112729	254.44	G/R 1/2	67,0	31,0	21
112730	254.45	G/R 3/4	73,0	33,0	25
112731	254.46	G/R 1	90,0	39,0	30



254.42

T-Stück, innen/innen/außen, AG: konisch DIN 2999, IG: zyl. nach DIN EN ISO 228-1

Artikel Nr.	Typen Nr.	Gewinde	L1 mm	L2 mm	SW mm
112732	254.71	G/R 1/8	39,5	21,0	10
112733	254.72	G/R 1/4	49,0	25,5	13
112734	254.73	G/R 3/8	54,0	28,0	17
112735	254.74	G/R 1/2	64,5	33,0	21
112736	254.75	G/R 3/4	69,5	36,5	25
112737	254.76	G/R 1	84,0	45,0	30



254.72

**NICHT DAS PASSENDE
GEFUNDEN?**

Alle Produktvarianten, Dokumenten-
und weitere Informationen
erhalten Sie auf Anfrage.